

ACMD-200

ACMD-200 is a wireless carbon monoxide (CO) detector that senses the dangerous concentration of this gas in a monitored room. It can work independently or as part of a two-way wireless **ABAX 2** system.

- electrochemical carbon monoxide detector
- digital temperature compensation
- test function
- LED for optical signalling
- piezoelectric transducer for acoustic signalling
- monitoring of the gas sensor
- battery status check
- operation in ABAX 2 wireless system:
 - encrypted two-way radio communication in the 868 MHz frequency band (AES standard)
 - diversification of transmission channels - 4 channels allow automatic selection of the channel that guarantees transmission without interference with other signals in the 868 MHz frequency band
 - ECO option for extended battery life
 - built-in temperature sensor (temperature measurement from 0 °C to +55 °C)
 - tamper protection against opening the enclosure

The detector is controlled by:

- **ACU-220** or **ACU-280** system controller
- **BE WAVE Hybrid** control panels
- **BE WAVE Smart HUB** controllers
- **ARU-200** signal retransmitter



Operating temperature range	0°C...+55°C
Max. current consumption	120 mA
Weight	153 g
Maximum humidity	93±3%
Operating frequency band	868,0 ÷ 868,6 MHz
Battery	CR123A 3 V
Dimensions	ø108 x 54 mm
Temperature measurement accuracy	±1 °C
Radio communication range (in open area) for ACU-220	do 2000 m
Radio communication range (in open area) for ACU-280	do 1200 m
Temperature measurement range	0°C...+55°C
Battery life (autonomous operation) - in years	do 5
Standby mode current consumption (autonomous operation)	14 µA
Expected battery life (ABAX 2) - in years	do 2
Standby current consumption (ABAX 2)	62
Low battery notification voltage	2,75 V