

AGD-200

The **AGD-200** detector is designed to detect the breaking of panes of regular, tempered and laminated glass. For detection, it uses advanced dual-path signal analysis. Sensitivity of its built-in microphone can be adjusted. The device works as part of the **ABAX 2** two-way wireless system.

Configuration of **AGD-200** and updating of its firmware are carried out remotely. Radio communication in the **ABAX 2** system is AES encrypted.

The detector is characterized by low energy consumption. It is powered by a CR123A 3 V lithium battery, whose status is constantly monitored. The "ECO" option extends the device operation time even fourfold without having to replace the battery.

The device is provided with a LED indicator of violations in the test mode, etc. Additionally, it comes with tamper protection against opening of the enclosure and removal from the mount.

The detector is available in white (**AGD-200**), brown (**AGD-200 BR**) and dark gray (**AGD-200 DG**).

- detection of breaking of regular, tempered and laminated glass panes
- advanced dual-path (multi-frequency) signal analysis
- compatible with*:
 - **ACU-220** and **ACU-280** system controllers
 - **BE WAVE Hybrid** control panels
 - **BE WAVE Smart HUB** controllers
 - **ARU-200** radio signal repeater
- range of radio communication in the open area – up to 2000 m*
- remote configuration and updating of the firmware
- detection sensitivity control
- built-in temperature sensor (temperature measurement in the range from -10°C to +55°C)
- LED indicator of violations in test mode
- low energy consumption and battery status check
- "ECO" option for extending battery life
- power supply: CR123A 3 V battery
- tamper protection against opening of the enclosure / removal from the mount

**detailed data available in the device manual*



Environmental class according to EN50130-5	II
Temperature measurement range	-10°C...+55°C
Radio communication range (in open area) for ACU-280	do 1200 m
Radio communication range (in open area) for ACU-220	do 2000 m
Radio communication range (in open area) for ACU-270	do 500 m
Radio communication range (in open area) for ACU-120	do 500 m
Detection range	do 6 m
Temperature measurement accuracy	±1°C
Complied with standards	EN 50130-4, EN 50130-5, EN 50131-5-3
Battery working time (in years)	do 2
Dimensions	20 x 102 x 23 mm
Standby current consumption	90 µA
Battery	CR123A 3 V
Operating frequency band	868,0 MHz - 868,6 MHz
Maximum humidity	93±3%
Weight	39 g
Max. current consumption	25 mA
Operating temperature range	-10°C...+55°C