

ASD-200

The device detects early signs of fire. It works as part of the **ABAX 2** two-way wireless system. Radio communication is AES encrypted.

The detector is equipped with a photoelectric visible smoke sensor placed in a special measuring chamber, whose unique design ensures high sensitivity of the detector. The precision Hexamesh stainless steel filter prevents particles of dirt and small insects from entering the chamber. The **ASD-200** also has a thermal sensor that reacts to exceeding the threshold of or a sudden increase in temperature. The alarm is signalled acoustically and optically. In addition, the detector controls the condition of the optical chamber: if it becomes clogged with dust, the LED indicates that maintenance is required.

ASD-200 is characterized by low energy consumption. This model is powered by a CR123A 3 V battery, whose status is monitored: voltage drop below a defined level is indicated visually and audibly. Additionally, the "ECO" option extends the device operation time even fourfold without having to replace the battery.

The device has tamper protection against opening of the enclosure.

- photoelectric sensor of visible smoke
- integrated thermal sensor
- acoustic and optical alarm signaling
- compatible with*:
 - **ACU-220** and **ACU-280** system controllers
 - **BE WAVE Hybrid** control panels
 - **BE WAVE Smart HUB** controllers
 - **ARU-200** radio signal repeater
- range of radio communication in the open area – up to 2000 m*
- remote firmware update
- unique Swirl chamber for quicker smoke detection
- Hexamesh precision stainless steel filter
- testing function
- chamber soiling indication
- low energy consumption and battery status check
- "ECO" option for extending battery life (in **ABAX 2** only)
- power supply: CR123A 3 V battery
- tamper protection against opening of the enclosure

**detailed data available in the device manual*



Standby current consumption	30 μ A
Low battery notification voltage	2,75 V
Static response temperature	54 °C
Temperature measurement range	0 °C...+55 °C
Radio communication range (in open area) for ACU-280	do 1200 m
Radio communication range (in open area) for ACU-220	do 2000 m
Radio communication range (in open area) for ACU-270	do 500 m
Radio communication range (in open area) for ACU-120	do 500 m
Temperature measurement accuracy	\pm 1 °C
Battery working time (in years)	do 2
Battery	CR123A 3 V
Operating frequency band	868,0 ÷ 868,6 MHz
Maximum humidity	93 \pm 3%
Weight	172 g
Max. current consumption	50 mA
Operating temperature range	0 °C...+55 °C
Enclosure dimensions	ϕ 108 x 61 mm