

INT-TSH-BSB

The **INT-TSH** keypad provides intuitive operation of alarm systems based on the control panels of **INTEGRA**, **INTEGRA Plus**, **VERSA** and **VERSA Plus** series. It comes with a large 7-inch touchscreen, which makes it an ideal solution for the users seeking as easy everyday operation of the alarm system as they know from their smartphones and tablets.

In addition to the basic commands for arming and disarming the system, the **INT-TSH** allows you to run even complex sequences of commands with just one command by using the **MACRO** function. This feature makes the keypad a great device to operate the alarm system including smart home functionality offered by the **INTEGRA** and **INTEGRA Plus** control panels.

The **INT-TSH** keypad provides also a quick and easy access to information about the current status of the system. With the large, readable widgets and the ability to define the information indicated in the status screen mode, it takes just one look at the device screen to find out what is happening in the protected premises. In addition, it is also possible to run a slide show on the keypad.



- keypad for **INTEGRA**, **INTEGRA Plus**, **VERSA** and **VERSA Plus** control panels (INTEGRA Firmware v1.14 or later, VERSA Firmware v1.06 or later)
- capacitive 7" touchscreen reacting even to a slight touch
- graphical user interface with color icons
- **MACRO** functions for easy control of the alarm system and home automation components (supported only by the **INTEGRA** and **INTEGRA Plus** control panels)
- customizable status screen to suit the user's preferences
- 2 zones (only supported by the **INTEGRA** and **INTEGRA Plus** control panels)
- **PANIC**, **FIRE**, **MEDICAL** alarms can be triggered from the keypad

| | |
|---|---------------------|
| Supply voltage | 12 V DC |
| Operating temperature range | -10°C...+55°C |
| Standby mode current consumption | 450 mA |
| Max. current consumption | 550 mA |
| Weight | 400 g |
| Maximum humidity | 93±3% |
| Environmental class according to EN50130-5 | II |
| Supported memory cards | microSD, micro SDHC |
| Enclosure dimensions (width x height x thickness) | 196 x 129 x 22 mm |