

SLIM-PIR

SLIM-PIR detects motion in the protected area. The device can be installed on the **BRACKET D** adjustable wall-and-ceiling mounting holder.

- certificate of compliance with the EN 50131 requirements for Grade 2
- motion detection using passive infrared (PIR) sensor
- adjustable sensitivity of detection
- digital motion detection algorithm
- digital temperature compensation
- wide-angle lens, designed specifically for the **SLIM LINE** detectors
- option to replace the wide-angle lens with a curtain (**CT-CL2**) or long-range (**LR-CL2**) one
- built-in end-of-line resistors (2EOL: 2 x 1.1 kΩ)
- LED indicator
- selectable color of the LED indicator (4 colors available)
- LED indicator remote enable/disable
- supervision of motion detection and supply voltage circuit
- tamper protection against opening of enclosure



Environmental class according to EN50130-5	II
Permissible installation height	do 4 m
Relay contact resistance (alarm output)	26 Ω
Tamper outputs (NC)	100 mA / 30 V DC
Alarm outputs (NC relay, resistive load)	40 mA / 24 V DC
Security grade according to EN50131-2-2	Grade 2
Warm-up period	30 s
EOL resistors	2 x 1,1 kΩ
Complied with standards	EN 50131-1, EN 50131-2-2, EN 50130-4, EN 50130-5
Alarm signaling time	2 s
Supply voltage	12 V DC
Dimensions	62 x 137 x 42 mm
Maximum humidity	93±3%
Weight	100 g
Max. current consumption	23 mA
Standby mode current consumption	8 mA
Recommended mounting height	2,4 m
Operating temperature range	-10°C...+55°C
Detected target velocity	0,3...3 m/s